


12510							
12610	12510TIN	12520	12562	12560	12564	12530	12540
DIN 335 C HSS	DIN 335 C HSS	DIN 335 D HSS	DIN 1866 HSSCO	DIN 373 HSSCO	≈ DIN 375 HSSCO	Norma Nui HSS	Norma Nui HSS
n° 3/90°	n° 3/90°	n° 3/90°	n° 3/90°	n° 3/180°	n° 3/180°	90°	90°
4,3:30	4,3:30	15:80	M3:M16	M3:M16	M8:M27	2-5:40-50	2-5:40-50
23	23	24	25	26	27	28	29
<p>neretto - bold = molto indicato - very suitable; corsivo - italic = indicato - suitable numero - number = m/min.; lettera - letter = avanzamenti - feeds; consultare tabella in fondo al capitolo - see table at the end of the chapter</p>							
30 D	40 D	30 D	25 C	25 C	25 C	30 C	30 C
25 C	35 C	25 C	20 C	20 C	20 C	25 B	25 B
20 C	30 C	20 C	18 B	18 B	18 B	20 B	20 B
15 B	20 B	15 B	15 B	15 B	15 B	15 A	15 A
10 B	15 C	10 B	10 B	10 B	10 B	10 A	10 A
12 B		12 B	8 B	8 B	8 B	12 A	12 A
10 B		10 B	4 B	4 B	4 B	10 A	10 A
8 B		8 B				8 A	8 A
5 A		5 A				5 A	5 A
20 D	30 D	20 D	20 D	20 D	20 D	20 C	20 C
12 D	18 D	12 D	10 C	10 C	10 C	12 C	12 C
10 B	15 B	10 B	10 C	10 C	10 C	10 A	10 A
8 B	12 B	8 B	8 C	8 C	8 C	8 A	8 A
5 A	8 A	5 A	5 C	5 C	5 C	6 A	6 A
10 B	15 B	10 B	10 B	10 B	10 B	10 A	10 A
5 A	8 B	5 A	5 A	5 A	5 A	6 A	6 A
1 A	2 A	1 A	1 A	1 A	1 A	1 A	1 A
25 C	35 C	25 C	20 B	20 B	20 B	25 B	25 B
20 C	30 C	20 C	18 B	18 B	18 B	20 B	20 B
25 D	35 D	25 D	20 B	20 B	20 B	25 C	25 C
12 C	15 C	12 C				12 A	12 A
30 E	40 E	30 E	25 D	25 D	25 D	30 C	30 C
25 D	35 D	25 D	20 D	20 D	20 D	25 B	25 B
20 C	30 C	20 C	18 D	18 D	18 D	20 B	20 B
8 B	12 B	8 B	8 C	8 C	8 C	8 A	8 A
30 D	40 D	30 D	25 B	25 B	25 B	30 C	30 C
20 C	30 C	20 C	15 B	15 B	15 B	20 B	20 B


**Norma
NUI**

12540
Codice - Code

Materiale - Material

Tolleranza del foro - Hole tolerance

Taglienti - Helical teeth

Rivestimento - Coating

HSSCO

90°

fori - holes Ø mm	D mm	L mm	CM	Prezzo Euro
2 - 5	10	90	1	44,72
5 - 10	14	95	1	47,37
10 - 15	21	120	2	68,69
15 - 20	27	130	2	94,12
20 - 25	35	135	2	138,54
25 - 30	44	165	3	229,14
30 - 35	48	170	3	300,45
35 - 40	53	180	3	395,06
40 - 50	64	190	3	564,27